

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006

**WIJZONOL**  
**BOUWVERVEN**  
**INTERNATIONAL B.V.**

**Product name :** Swedish Putty  
**Revision :** 05.11.2010      **Version :** 4.0.0  
**Print date :** 05-11-2010

## 01. Identification of substance, product and company

### Product name:

Swedish Putty

### Use of the substance / product

Swedish putty is a traditional, ultra-fine knifing filler suitable for interior and exterior use on all wood, metal and wall surfaces.

### Manufacturer/Supplier

Wijzonol Bouwverven International B.V.

### Street/P.O.Box

Russenweg 14

### Country code/Postal code/Town/City

8041 AL ZWOLLE

### Telephone / Telefax (weekdays 8-5 C.E.T.)

+31 (0)38-4291100 / +31 (0)38-4291149

### Emergency information

No additional information available.

## 02. Hazards identification

### Hazard designation

Flammable · Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Classification : R 10 · R 52/53

## 03. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

### Hazardous components

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY ; EC-No. : 265-185-4; CAS-No. : 64742-82-1

Percentage : 5 - 10 %

Classification 67/548/EEC : N ; R51/53 Xn ; R65 R67 R66

QUARTZ (SiO<sub>2</sub>) ; EC-No. : 238-878-4; CAS-No. : 14808-60-7

Percentage : 1 - 5 %

Classification 67/548/EEC : Xn ; R48/20

XYLENE ; EC-No. : 215-535-7; CAS-No. : 1330-20-7

Percentage : 1 - 5 %

Classification 67/548/EEC : R10 Xn ; R20/21 Xi ; R38

Classification 1272/2008 (GHS) : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315

NAPHTHA (PETROLEUM), HYDROTREATED HEAVY ; EC-No. : 265-150-3; CAS-No. : 64742-48-9

Percentage : 1 - 5 %

Classification 67/548/EEC : R10 Xn ; R65 R66

Classification 1272/2008 (GHS) : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT / KEROSENE - UNSPECIFIED ; EC-No. : 265-149-8; CAS-No. : 64742-47-8

Percentage : 1 - 5 %

Classification 67/548/EEC : Xn ; R65

Classification 1272/2008 (GHS) : Asp. Tox. 1 ; H304

ETHOXYLATED NONYLPHENOL ; CAS-No. : 68412-54-4

Percentage : 1 - 5 %

Classification 67/548/EEC : N ; R51/53 Xi ; R41 Xn ; R22 Xi ; R38

1,2,4-TRIMETHYLBENZENE ; EC-No. : 202-436-9; CAS-No. : 95-63-6

Percentage : 1 - 2,5 %

Classification 67/548/EEC : R10 N ; R51/53 Xn ; R20 Xi ; R36/37/38

Classification 1272/2008 (GHS) : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335 Aquatic Chronic 2 ; H411

For the wording of the listed risk phrases refer to section 16.

## 04. First-aid measures

### General

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006

**WIJZONOL**  
**BOUWVERVEN**  
**INTERNATIONAL B.V.**

**Product name :** Swedish Putty  
**Revision :** 05.11.2010      **Version :** 4.0.0  
**Print date :** 05-11-2010

---

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

#### **After inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconsciousness, place in recovery position and seek medical attention.

#### **After skin contact**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleaner. Do NOT use solvents or thinners.

#### **After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

#### **After ingestion**

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

---

### **05. Fire-fighting measures**

#### **Suitable extinguishing media**

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray.

#### **Unsuitable extinguishing media**

Waterjet.

#### **Special risk posed by the substance or by the actual product, its combustion products or gases discharged**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

#### **Special protective equipment**

Appropriate breathing apparatus may be required. For fighting fires in buildings and confined spaces, firefighters must use self-contained breathing apparatus and should wear full fire-fighting turn-out gear.

#### **Additional information**

Cool closed containers exposed to fire with water. Do not allow run-off from the fire fighting to enter drains of waterways.

---

### **06. Accidental release measures**

#### **Personal precautions**

Eliminate sources of ignition and ventilate the area. Avoid breathing vapors. Refer to protective measures listed in sections 7 and 8.

#### **Environmental precautions**

Do not empty into drains. If the product is accidentally released into lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

#### **Methods for cleaning up/collecting**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

---

### **07. Handling and storage**

#### **Information for safe handling**

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentrations higher than the OEL (Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been eliminated. Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Product may charge electrostatically: always ground containers when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Keep the container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates and spray mist arising from the application of this product. Avoid inhalation of dust from sanding.

Smoking, eating and drinking should be prohibited in application area.

For personal protection see Section 8.

Never use pressure to empty: container is not a pressure vessel.

Always keep in containers of same material as the original one.

Comply with the health and safety at work laws.

#### **Further information about storage conditions**

Storage in accordance with CPR 15-1 or CPR 15-2. Observe label precautions. Store between 0 and 35 degrees C. (32 and 95 degrees F.) in a dry, well ventilated place away from sources of heat and direct sunlight.

Keep away from oxidizing agents, strongly alkaline and strongly acidic materials. No smoking. Prevent unauthorized access.

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not allow to enter drains.

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006

**WIJZONOL**  
**BOUWVERVEN**  
**INTERNATIONAL B.V.**

**Product name :** Swedish Putty  
**Revision :** 05.11.2010      **Version :** 4.0.0  
**Print date :** 05-11-2010

## 08. Exposure controls and personal protection

### Additional information about engineering measures

Provide adequate ventilation. Where reasonably practical this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations below the OEL (Occupational Exposure Limit), suitable respiratory protection must be worn.

### Components with critical values that require monitoring at the workplace (exposure limits)

XYLENE ; CAS-No. : 1330-20-7

Specification : Limit value (Short term) ( EC )  
Value : 100 ppm / 442 mg/m<sup>3</sup>  
Remarks : H  
Version date : 08-06-2000

Specification : Limit value (8 hours) ( EC )  
Value : 50 ppm / 221 mg/m<sup>3</sup>  
Remarks : H  
Version date : 08-06-2000

1,2,4-TRIMETHYLBENZENE ; CAS-No. : 95-63-6

Specification : Limit value (8 hours) ( EC )  
Value : 20 ppm / 100 mg/m<sup>3</sup>  
Version date : 08-06-2000

Specification : NIOSH REL TWA ( USA )  
Value : 25 ppm  
Version date : 01-01-2003

### Personal protective equipment

#### Respiratory protection

If workers are exposed to concentrations above the exposure limit, they must use a NIOSH-approved respirator.

#### Hand protection

Solvent-resistant gloves may be appropriate gloves.

#### Eye protection

Safety glasses or goggles may be appropriate.

#### Body protection

Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

## 09. Physical and chemical properties

### Relevant safety data

<b>Physical state :</b>	liquid
<b>Appearance :</b>	high build viscous liquid
<b>Boiling point / range :</b>	( 1013 hPa ) no data available
<b>Boiling point hPa (Fahrenheit) :</b>	( 1013 hPa ) no data available.
<b>Flashpoint :</b>	38 °C      Closed cup
<b>Flashpoint [Fahrenheit] :</b>	104 °F      Closed cup
<b>Lower explosion limit :</b>	no data available
<b>Upper explosion limit :</b>	no data available
<b>Specific gravity :</b>	( 20 °C / 68 °F ) 1,8 g/cm <sup>3</sup>
<b>Solvent-separation test :</b>	( 20 °C / 68 °F ) no data available
<b>Solubility in water :</b>	( 20 °C / 68 °F ) insoluble

## 10. Stability and reactivity

### Conditions to avoid

Stable under recommended storage and handling conditions (See section 7).

### Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acidic materials to avoid exothermic reactions.

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006

**WIJZONOL**  
**BOUWVERVEN**  
**INTERNATIONAL B.V.**

**Product name :** Swedish Putty  
**Revision :** 05.11.2010      **Version :** 4.0.0  
**Print date :** 05-11-2010

---

## 11. Toxicological information

There are no data available on the product itself. The product has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

### Health effects from exposure:

Inhalation: May irritate mucous membranes, produce a narcotic effect, impair reaction time or coordination.

Eye Contact: May cause irritation.

Skin contact: May cause irritation and be absorbed through skin.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the product may cause defatting of the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

Liquid splashed in the eyes may cause irritation and reversible damage.

---

## 12. Ecological information

There are no data available on the product itself.

The product should not be allowed to enter drains or waterways.

---

## 13. Disposal considerations

Do not empty into waters or drains. Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

---

## 14. Transport information

### Land transport ADR/RID

#### Classification

**Class :** 3      **Kemlercode :** 30  
**UN number :** 1263      **Classification-Code :** F1

ADR : - (<= 450 l) · Special provisions : 640E · LQ 7 · E 1 · Tunnel restriction code : D/E

#### Proper shipping name

PAINT

#### Packaging

**Packaging group :** III  
**Label :** 3

### Maritime transport IMDG/GGVSea

#### Classification

**IMDG-Code :** 3      **EmS number :** F-E / S-E  
**UN number :** 1263      **Marine Poll. :** -

IMDG 2.3.2.5 (<= 30 l) · LQ 5 I · E 1

#### Proper shipping name

PAINT

#### Packaging

**Packaging group :** III  
**Label :** 3

### Air transport ICAO-TI and IATA-DGR

#### Classification

**Class :** 3  
**UN number :** 1263

E 1

#### Proper shipping name

PAINT

#### Packaging

**Packaging group :** III  
**Label :** 3

---

## 15. Regulatory information

### Labelling (67/548/EEC or 1999/45/EC)

#### R-phrases

10      Flammable  
52/53      Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006

**WIJZONOL**  
**BOUWVERVEN**  
**INTERNATIONAL B.V.**

**Product name :** Swedish Putty  
**Revision :** 05.11.2010      **Version :** 4.0.0  
**Print date :** 05-11-2010

## S-phrases

- 57 Use appropriate container to avoid environmental contamination.  
61 Avoid release to the environment. Refer to special instructions/Safety data sheets.  
35 This material and its container must be disposed of in a safe way  
51 Use only in well-ventilated areas.

## International regulatory information

U.S. Federal Regulations  
Toxic Substances Control Act (TSCA) status: All ingredients are on the TSCA Inventory or excluded from TSCA.

**Occupational Safety and Health Administration (OSHA):** Hazard Communication Standard (HCS) Class II Combustible liquid. This product is considered a hazardous substance as defined by the OSHA HCS. Primary routes of entry: Inhalation, skin contact, eye contact. Use of NIOSH-approved respiratory protection is recommended during sanding.

The following OSHA PELs/ACGIH TLVs apply to the ingredients listed in Section 3:

Xylene:	OSHA PEL: 100 ppm TWA; ACGIH TLV: 100 ppm TWA; 150 ppm STEL.
Quartz (crystalline silica):	OSHA PEL: 30 mg/m <sup>3</sup> / %SiO <sub>2</sub> (total dust), 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> (respirable fraction); ACGIH TLV: 0.025 mg/m <sup>3</sup> (respirable).

In addition, the following ingredients are listed in 29 CFR Part 1910, subpart Z:

Calcium carbonate	1317-65-3	215-279-6	20 – 30 OSHA PEL: 15 mg/m <sup>3</sup> (total dust), 5 mg/m <sup>3</sup> (respirable fraction).
Kaolin	1318-74-4	310-194-1	2.5 – 10 OSHA PEL: 15 mg/m <sup>3</sup> (total dust), 5 mg/m <sup>3</sup> (respirable fraction); ACGIH TLV: 2 mg/m <sup>3</sup> (respirable fraction)
Mica	12001-26-2	-----	1 - 2.5 OSHA PEL: 20 mmpcf (silicates); ACGIH TLV: 3 mg/m <sup>3</sup> (respirable fraction)
Titanium dioxide	13463-67-7	236-675-5	1 - 2.5 OSHA PEL: 15 mg/m <sup>3</sup> (total dust), ACGIH TLV: 10 mg/m <sup>3</sup>
Barium sulfate	7727-43-7	231-784-4	1 - 2.5 OSHA PEL: 15 mg/m <sup>3</sup> (total dust), ACGIH TLV: 10 mg/m <sup>3</sup>

## OSHA Listed Carcinogens:

Silica, crystalline: IARC: Group 1/NTP: Known to be a human carcinogen  
Titanium dioxide: IARC: Group 2B, Possibly Carcinogenic to humans

## US State Regulations:

**California Proposition 65:** This product contains a chemical known to the State of California to cause cancer.

**State Right-to-Know Regulations:** Contains ingredients listed under state right-to-know laws: New Jersey Community Right-to-Know Act, Massachusetts Hazardous Substances Disclosure by Employers Act, Pennsylvania Worker and Community Right-to-Know Act, Michigan Natural Resources and Environmental Protection Act, Illinois Toxic Substances Disclosure to Employees

## 16. Other information

### Further information

The details in this material safety data sheet satisfy the U.S. Occupational Safety and Health Administration Hazard Communication Standard and legislation in the Netherlands and the European Union. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

### Relevant changes

14. Land transport ADR/RID and GGVS/GGVE (2003) · 14. Classification (ADR) · 14. Proper shipping name (ADR) · 14. Maritime transport IMDG/GGVSea · 14. Classification (IMDG) · 14. Technical name (IMDG) · 14. Air transport ICAO-TI and IATA-DGR · 14. Classification (ICAO) · 14. Technical name (ICAO) · 15. R-phrases · 15. S-phrases

### R-Phrases of components

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006

**WIJZONOL**  
**BOUWVERVEN**  
**INTERNATIONAL B.V.**

**Product name :** Swedish Putty  
**Revision :** 05.11.2010      **Version :** 4.0.0  
**Print date :** 05-11-2010

---

10	Flammable.
20	Harmful by inhalation.
20/21	Harmful by inhalation and in contact with skin.
22	Harmful if swallowed.
36/37/38	Irritating to eyes, respiratory system and skin.
38	Irritating to skin.
41	Risk of serious damage to eyes.
48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapors may cause drowsiness and dizziness

**Department issuing data sheet**

Chemtrec emergency hazardous information (Chemtrec@americanchemistry.com):  
Domestic / North America: 800-424-9300  
International: 703-527-3887 (call collect)

---

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

---